

(11)Publication number:

10-242513

(43)Date of publication of application: 11.09.1998

(51)Int.CI.

H01L 33/00

G09F 9/00

(21)Application number: 09-218149

HO4N 5/66

(22)Date of filing:

28.07.1997

(71)Applicant:

(72)Inventor:

NICHIA CHEM IND LTD

SHIMIZU YOSHINORI

SAKANO AKIMASA

(30)Priority

Priority number: 08198585

Priority date: 29.07.1996

Priority country: JP

JP

08245381 08359004


18.09.1996 27.12.1996

JP

(54) LIGHT EMITTING DIODE AND DISPLAY DEVICE USING THE SAME

(57)Abstract:

PROBLEM TO BE SOLVED: To reduce the luminous efficiency deterioration and color slurring of a light emitting diode even when the diode is used for a long time under a high-luminance condition, by respectively constituting the LED chip and photoluminescent phosphor of the diode of a nitride compound semiconductor and cerium-reactivated yttrium aluminum garnet phosphor. SOLUTION: An LED chip 202 using a gallium nitride semiconductor is fixed in an enclosure 204 of a chip type LED with an epoxy resin, etc. An epoxy resin in which a (RE1-xSmx)3(AlyGa1-y)5012: Ce phosphor is scattered is uniformly cured as a molded member 201 which protects the LED chip 202, conductive wires, etc., from the external stresses. The cerium-reactivated yttrium aluminum garnet phosphor is scattered in the epoxy resin as a photoluminescent phosphor.



LEGAL STATUS

[Date of request for examination]

11.10.1997

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

2927279

[Date of registration]

14.05.1999

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of

rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japanese Patent Office